

SYSTEM 500 PACK

Installation & use instructions
MOUNTING & BACK DOOR



1A Orient tabs

Position the mounting tabs to balance the loaded pack.



1B Seat tabs

Insert tabs into the pack slots until side by side and flush with the pack surface.



2 Adjust fit

If needed, remove one or both tension dots from the mounting tab.



3 Attach pack

Attach to the Action Mount using the kit. Use cloth pouch and/or foam to reduce vibration.



4 Insert door

Align and insert the back door into the notched opening.



5 Lock door

Support the bottom of the pack. Push the door downward until locked.



6 Adjust tension

Tighten or loosen the back door screws to adjust attachment tension.

USE & CARE

Back door removal, accessories and important notes



7 Release latch

To open, depress and hold the bottom latch tab first.



8 Slide door up

Support the top of the pack and slide the back door upward.



9 Use a tether

Connect the radar to the saddle rails with a device tether (not included).



10 Support parts

Support the pack and back door while attaching or removing the device.

IMPORTANT NOTES

- Do not expose the pack to prolonged periods of extreme heat.
- Remove the pack from the bike when using a car rack or carrier.
- The Action Mount must support the combined weight of the pack, its contents (less than 500 g), and the radar.
- To adjust alignment with the seatpost or saddle, loosen the Action Mount bolts, reposition the pack, then retighten the bolts.
- When fitted correctly, the back door aligns with the pack on all sides. Release the bottom latch before removing the door.
- Clean with mild soap and water, then dry thoroughly with a clean cloth. Do not use abrasive cleaners.
- Periodically check that the back door is securely latched and all attachment bolts are properly tightened.